

FILENAME

REVDATE

USER

4

3

2

1

D

C

B

A

D

C

B

REVISIONS			
REV	DESCRIPTION	CHK	ENG DATE
1-a			
1-b		HU	07/18/04

9.53 [3/8-16NC]

R0.75 [R0.030"]

R0.75 [R0.030"]

5.6(7/32")

ø3/8" 16THREADS PER INCH

17.40 [0.685"]


1.50 [0.059"]

20.00 [0.787"]

3.00^{+0.00}_{-0.08} [0.118^{+0.000"}_{-0.003"}]

NOTES:

1. MATERIAL:STAINLESS STEEL _304
HEAT TREATMENT: POST PLATE THROUGH HARDENED TO HRC 20--35
- 2 FINISH: DULL BLACK ZINC
PART SHALL EXHIBIT NO RED RUST AFTER 600HR
SALT-FOG TEST PER ASTM B117.
- 3 Thread of parts shall be tested by "pass" gage and " reject" gage.
- 4 Assembly predrive torque 1.6?0.2N-M
- 5 PART TO BE CLEAN AND FREE OF OILS AND LUBRICANTS

Unless otherwise specified dimensions are in millimeter. Tolerances are: Decimals Angles X. +/- +/- .X +/- 0.20 .XX +/- 0.10	THIRO ANGLE PROJECTION		LEVEL	DRAFTER	DATE:	ELDER AUDIO MANUFACTORY						
			3	HU	12/3/02	The Third Industict District Wentang Dongguan Guangdong 523121 China.						
				CHECKER		DESCRIPTION						
	MATERIAL: See Notes		2	ENGINEER	12/3/02	PT298591						
FINISH: See Notes		1	HU	SCREW,3/8-16,LT-III,BLK,SERVICE								
			APP BY		SIZE	C	FSCM	CLASS	DWG NO.:	B-LS10-02	REV	1
					SCALE: NONE				LT9702-II-1-109		SHEET 1 of 1	