REVISIONS				
REV	DESCRIPTION	CHK	ENG	DATE
1-a				
1-b			HU	07/18/04



NOTES:

1. MATERIAL:STAINLESS STEEL
   HEAT TREATMENT: POST PLATE THROUGH HARDENED TO HRC 20--35
2. FINISH: DULL BLACK ZINC
   PART SHALL EXHIBIT NO RED RUST AFTER 600HR
   SALT-FOG TEST PER ASTM B117.
3. Thread of parts shall be tested by "pass" gage and " reject" gage.
4. PART SHALL WITHSTAND 57.5 IN-LB(6.5N-M)MIN.TORSIONAL STRENGTH
5. Assembly predrive torque 1.8?0.2N-M

Unless otherwise specified dimensions are in millmeter. Tolerances are: Decimals Angles X. +/— +/— .X +/- 0.20 .XX+/- 0.10	THIRD ANGLE PROJECTION	LEVEL 3	DRAFTER HU	DATE: 12/3/02	ELDER AUDIO MANUFACTORY The Third Industrict District Wentang Dongguan Guangdong 523121 China.
	MATERIAL: See Notes	2	CHECKER		DESCRIPTION BOSELT9702-II TM5X22
	FINISH: See Notes	1	ENGINEER HU	12/3/02	SIZE C FSCM CLASS DWG NO.:B2-LS5-01 LT9702-II-2-111 REV 1-b
			APP BY		SCALE: NONE SHEET of

FNAME REVDATE USER